

IDG-712G2

Long Range Integrated Reader (Dedicated for Parking)

Features

- **Long Range Identification:** Adjustable up to 15 meter, can scan the tag through the explosion-proof membrane;
- **Integrated Structure:** Simple to install (Bow-free installation), easy to use;
- **Unique Design:** Streamline design style, can make OEM Logo;
- **Bran-new Function:** Swipe tips device upgrades, more bright and beautiful;
- **Dedicated Software Functions:** Dedicated software function for parking, thus reducing secondary development and integration work;
- **A Variety of Operating Modes:** Time, induction triggering, data triggering;
- **Anti Mutual Interference Features:** Multiple devices can work simultaneously;
- **Good Expansibility:** Reserving a variety of interfaces to accommodate changes in system requirements;
- **Full Industrial Design:** IP54, resistance to high and low temperature, EMC, suitable for harsh industrial environments.

Specifications

| | |
|------------------------------|--|
| Frequency | 919~923MHz |
| Supported RFID Tag Protocols | EPC C1 Gen2(ISO18000-6C), or ISO18000-6B |
| Communication Interface | Wiegand 26/34, RS232 or RS485 or LAN (RJ45, TCP/IP) |
| Read and Write Performance | Straight line identification distance > Adjustable up to 15 meter |
| Supply Power | DC 12V/3A |
| Operating Temperature | -20 ~ +70°C |
| Storage Temperature | -40 ~ +85°C |
| Dimension | 370mm x 360mm x 96mm |
| Net Weight | 3.3 kg |

