

# TW-HDMI-HDSP0009M1

## HDMI Splitter 1x4 V2.0



### Features

- One HDMI 2.0 input signal split to four HDMI 2.0 sink devices
- Support HDR
- Support 4K\*2K @60Hz resolution
- Support deep color 24bit, 30bit, 36bit
- Video Format Support: 4Kx2K/60Hz YcbCr 4:4:4
- Support Blue-Ray 24/50/60fs/HD-DVD/xvYCC
- Digital audio format, as DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
- The HDMI Input Cable distance can be up to 10m and HDMI Output Cable distance can be up to 10 when transmit the 1080P signal by using standard AWG24 HDMI Cable; The HDMI Input Cable distance can be up to 5m and HDMI Output Cable distance can be up to 5m when transmit the 4Kx2Knal by using standard AWG24 HDMI Cable;
- Support signal retiming
- No loss of quality
- Installs in minutes
- Need DC5V/2A power supply

### Specification

- HDMI resolution: 4K@60Hz /4K@30Hz/3D/1080P/1080i/720p /576p/576i/480P/480i
- Support video color format: 24bit/deep color 30bit,36bit
- Support audio format: DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD
- Input cable distance: ≤10m(1080P)/5M(4K) AWG24 HDMI standard cable
- Output cable distance: ≤10m(1080P)/5M(4K) AWG24 HDMI standard cable
- Power adapter format: Input: AC (50HZ, 60HZ) :100V-240V; Output: DC5V/2A
- Operating Temperature range: -0 to +40°C
- Storage Temperature range: -20 to +60°C
- Operating Humidity range: 5 to 85%RH (No Condensation)
- Storage Humidity range: 5 to 95%RH (No Condensation)
- Max bandwidth: 600MHz
- Max baud rate: 18Gbps
- Dimension (L x W x H): 139X64X22(mm)
- Weight: 220g
- Max working current: 1000mA
- Input/Output TMDS signal: 0.5~1.5Volts p-p(TTL)
- Input/Output DDC signal: 5Volts p-p (TTL)

### Dimension

